

| | |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product: | InvisiFreeze™ S (GN2/1) |
| Manufacturer: | Gastros Switzerland AG |
| Category: | Undercounter Cooling Device |
| Image: |  |
| Tender-Text: | <p>InvisiFreeze™ S</p> <p>Undercounter cooling unit with external control unit for installation under various surfaces such as glass or artificial stone, analogue and suitable for the InductWarm® 130+ Undercounter Warming Unit.</p> <p>The device cools the surface on four selectable cooling levels: Cool (cold surface), Chill, Cold and Freeze (ice layer). The InvisiFreeze™ will be operated via an optional, external control unit (article number: 6 60 500 01). Up to 16 devices can be daisy-changed via a BUS cable and operated synchronously with just one panel (all devices on the same cooling level). The built-in USB interface allows software updates as well as the reading of operating data for remote diagnostics. The current operating status and the cooling-levels are indicated by four LEDs. The appropriate surface panel can be selected individually to match the customer's design wishes, and Gastros will be happy to make recommendations.</p> <p>The InvisiFreeze™ must be bonded to the surface material with an adhesive supplied.</p> |

| Article no: | Cooling zones | Dimensions | Weight | Power supply | max. power |
|-------------|---------------|--------------------|--------|--------------|------------|
| 1 60 100 01 | 1 GN2/1 | 670 x 530 x 367 mm | 21 kg | 230 V AC | 0.3 kW |